



[CWINE]1

TECHNICAL SPECIFICATIONS

STORAGE RECOMMENDATIONS:

The recommended storage time and use of the stoppers is of 6 months since the manufacturing date. Storage should be under original packaging. Avoid the cork stoppers from coming into contact with chemical products, pesticides, fungicides, chlorine-based sanitary products and treated wooden structures (in particular PCP- Pentachlorophenol's). Do not store directly on the floor. Do not expose to sunlight, even through glass. In case of any doubt or comments please do not hesitate to contact us at trefinos@trefinos.es



CHARACTERISTICS		VALUES		SPECIFICATION	METHODOLOGY
DIMENSIONAL	LENGTH	Nom. value	mm	± 0,5	UNE 56933
	DIAMETER	Nom. value	mm	± 0,3	UNE 56933
	CHAMFER	1,5 x 1,5	mm		
PHYSICAL	DENSITY	290	Kg/m ³	± 20	UNE 56933
	HUMIDITY	5,5	%	± 1,5	UNE 56933
	RESIDUAL DUST	0,001	g/stopper	Max.	UNE 56933
	WATER ABSORPTION	10	% Δ weight	Max.	MI 98 IN CC
	CORK PERCENTAGE	75	%	Min.	T-IF-02
MECHANICS	DIMENSIONAL RECOVERY (5 min)	95	%	Min.	UNE 56933
	EXTRACTION FORCE	25	daN	± 10	UNE 56933
	COMPRESSION FORCE	140	daN	± 15	88 IN CC
CHEMICAL	RESIDUAL PEROXIDE	0,2	mg/stopper	Max.	UNE 56929
	GLOBAL MIGRATION	10	mg/dm2	Max.	UNE-ISO 10106
MICROBIOLOGIC	BACTERIA	30	UFC/ stopper	Max.	UNE 56923
	MOLD AND YEAST	10	UFC/ stopper	Max.	UNE 56923
PERMEABILITY	O.T.R.	4,5	μl O ₂ /day		Oxo-luminiscence
SPME/ GC/ MS ANALYSIS	2,4,6 –TCA,	< LQ (*)	ng/L	Individual	UNE 56930
	2,3,4,6 –TeCA, PCA ,Guayacol, Geosmina, Octanol, metilisoborneol, 2- isopropil-3metoxipirazina	< LD	ng/L	< LD	External
SENSORY	SENSORY DESVIATIONS	AQL 0.65. Method: water maceration.			

(*) LQ: Quantification limit : <0, 3 ng/L

The products used for the manufacturing this product do not contain genetically modified organisms (GMOs) or allergens.





[CWINE]2

TECHNICAL SPECIFICATIONS

STORAGE RECOMMENDATIONS:

The recommended storage time and use of the stoppers is of 6 months since the manufacturing date. Storage should be under original packaging. Avoid the cork stoppers from coming into contact with chemical products, pesticides, fungicides, chlorine-based sanitary products and treated wooden structures (in particular PCP- Pentachlorophenol's). Do not store directly on the floor. Do not expose to sunlight, even through glass. In case of any doubt or comments please do not hesitate to contact us at trefinos@trefinos.es



CHARACTERISTICS		VALUES		SPECIFICATION	METHODOLOGY
DIMENSIONAL	LENGTH	Nom. value	mm	± 0,5	UNE 56933
	DIAMETER	Nom. value	mm	± 0,3	UNE 56933
	CHAMFER	1,5 x 1,5	mm		
PHYSICAL	DENSITY	290	Kg/m ³	± 20	UNE 56933
	HUMIDITY	5,5	%	± 1,5	UNE 56933
	RESIDUAL DUST	0,001	g/stopper	Max.	UNE 56933
	WATER ABSORPTION	9	% Δ weight	Max.	MI 98 IN CC
	CORK PERCENTAGE	75	%	Min.	T-IF-02
MECHANICS	DIMENSIONAL RECOVERY (5 min)	95	%	Min.	UNE 56933
	EXTRACTION FORCE	25	daN	± 10	UNE 56933
	COMPRESSION FORCE	140	daN	± 15	88 IN CC
CHEMICAL	RESIDUAL PEROXIDE	0,2	mg/stopper	Max.	UNE 56929
	GLOBAL MIGRATION	10	mg/dm2	Max.	UNE-ISO 10106
MICROBIOLOGIC	BACTERIA	30	UFC/ stopper	Max.	UNE 56923
	MOLD AND YEAST	10	UFC/ stopper	Max.	UNE 56923
PERMEABILITY	O.T.R.	2,7	μl O ₂ /day		Oxo-luminiscence
SPME/ GC/ MS ANALYSIS	2,4,6 –TCA,	< L.Q (*)	ng/L	Individual	UNE 56930
	2,3,4,6 –TeCA, PCA ,Guayacol, Geosmina, Octanol, metilisoborneol, 2- isopropil-3metoxipirazina	< LD	ng/L	< LD	External
SENSORY	SENSORY DESVIATIONS	AQL 0.65. Method: water maceration.			

(*) LQ: Quantification limit : <0, 3 ng/L

The products used for the manufacturing this product do not contain genetically modified organisms (GMOs) or allergens.





[CWINE]3

TECHNICAL SPECIFICATIONS

STORAGE RECOMMENDATIONS:

The recommended storage time and use of the stoppers is of 6 months since the manufacturing date. Storage should be under original packaging. Avoid the cork stoppers from coming into contact with chemical products, pesticides, fungicides, chlorine-based sanitary products and treated wooden structures (in particular PCP- Pentachlorophenol's). Do not store directly on the floor. Do not expose to sunlight, even through glass. In case of any doubt or comments please do not hesitate to contact us at trefinos@trefinos.es



CHARACTERISTICS		VALUES		SPECIFICATION	METHODOLOGY
DIMENSIONAL	LENGTH	Nom. value	mm	± 0,5	UNE 56933
	DIAMETER	Nom. value	mm	± 0,3	UNE 56933
	CHAMFER	1,5 x 1,5	mm		
PHYSICAL	DENSITY	290	Kg/m ³	± 20	UNE 56933
	HUMIDITY	5,5	%	± 1,5	UNE 56933
	RESIDUAL DUST	0,001	g/stopper	Max.	UNE 56933
	WATER ABSORPTION	7	% Δ weight	Max.	MI 98 IN CC
	CORK PERCENTAGE	75	%	Min.	T-IF-02
MECHANICS	DIMENSIONAL RECOVERY (5 min)	95	%	Min.	UNE 56933
	EXTRACTION FORCE	25	daN	± 10	UNE 56933
	COMPRESSION FORCE	140	daN	± 15	88 IN CC
CHEMICAL	RESIDUAL PEROXIDE	0,2	mg/stopper	Max.	UNE 56929
	GLOBAL MIGRATION	10	mg/dm2	Max.	UNE-ISO 10106
MICROBIOLOGIC	BACTERIA	30	UFC/ stopper	Max.	UNE 56923
	MOLD AND YEAST	10	UFC/ stopper	Max.	UNE 56923
PERMEABILITY	O.T.R.	1,9	μl O ₂ /day		Oxo-luminiscence
SPME/ GC/ MS ANALYSIS	2,4,6 –TCA,	< L.Q. (*)	ng/L	Individual	UNE 56930
	2,3,4,6 –TeCA, PCA ,Guayacol, Geosmina, Octanol, metilisoborneol, 2- isopropil-3metoxipirazina	< LD	ng/L	< LD	External
SENSORY	SENSORY DESVIATIONS	AQL 0.65. Method: water maceration.			

(*) LQ: Quantification limit : <0, 3 ng/L

The products used for the manufacturing this product do not contain genetically modified organisms (GMOs) or allergens.





[CWINE]

montebello

TECHNICAL SPECIFICATIONS

STORAGE RECOMMENDATIONS:

The recommended storage time and use of the stoppers is of 6 months since the manufacturing date. Storage should be under original packaging. Avoid the cork stoppers from coming into contact with chemical products, pesticides, fungicides, chlorine-based sanitary products and treated wooden structures (in particular PCP- Pentachlorophenol's). Do not store directly on the floor. Do not expose to sunlight, even through glass. In case of any doubt or comments please do not hesitate to contact us at trefinos@trefinos.es



CHARACTERISTICS		VALUES		SPECIFICATION	METHODOLOGY
DIMENSIONAL	LENGTH	Nom. value	mm	± 0,5	UNE 56933
	DIAMETER	Nom. value	mm	± 0,3	UNE 56933
	CHAMFER	1,5 x 1,5	mm		
PHYSICAL	DENSITY	290	Kg/m ³	± 20	UNE 56933
	HUMIDITY	5,5	%	± 1,5	UNE 56933
	RESIDUAL DUST	0,001	g/stopper	Max.	UNE 56933
	WATER ABSORPTION	10	% Δ weight	Max.	MI 98 IN CC
	CORK PERCENTAGE	75	%	Min.	T-IF-02
MECHANICS	DIMENSIONAL RECOVERY (5 min)	95	%	Min.	UNE 56933
	EXTRACTION FORCE	25	daN	± 10	UNE 56933
	COMPRESSION FORCE	140	daN	± 15	88 IN CC
CHEMICAL	RESIDUAL PEROXIDE	0,2	mg/stopper	Max.	UNE 56929
	GLOBAL MIGRATION	10	mg/dm2	Max.	UNE-ISO 10106
MICROBIOLOGIC	BACTERIA	30	UFC/ stopper	Max.	UNE 56923
	MOLD AND YEAST	10	UFC/ stopper	Max.	UNE 56923
SPME/ GC/ MS ANALISIS	2,4,6 –TCA,	1,9	ng/L	Max.	UNE 56930
	2,3,4,6 –TeCA, PCA ,Guayacol, Geosmina, Octanol, metilisoborneol, 2- isopropil-3metoxipirazina	< LD	ng/L	< LD	External
SENSORY	SENSORY DESVIATIONS	AQL 0.65. Method: water maceration.			

The products used for the manufacturing this product do not contain genetically modified organisms (GMOs) or allergens.





[CWINE]
montebello +

TECHNICAL SPECIFICATIONS

STORAGE RECOMMENDATIONS:

The recommended storage time and use of the stoppers is of 6 months since the manufacturing date. Storage should be under original packaging. Avoid the cork stoppers from coming into contact with chemical products, pesticides, fungicides, chlorine-based sanitary products and treated wooden structures (in particular PCP- Pentachlorophenol's). Do not store directly on the floor. Do not expose to sunlight, even through glass. In case of any doubt or comments please do not hesitate to contact us at trefinos@trefinos.es



CHARACTERISTICS		VALUES		SPECIFICATION	METHODOLOGY
DIMENSIONAL	LENGTH	Nom. value	mm	± 0,5	UNE 56933
	DIAMETER	Nom. value	mm	± 0,3	UNE 56933
	CHAMFER	1,5 x 1,5	mm		
PHYSICAL	DENSITY	290	Kg/m ³	± 20	UNE 56933
	HUMIDITY	5,5	%	± 1,5	UNE 56933
	RESIDUAL DUST	0,001	g/stopper	Max.	UNE 56933
	WATER ABSORPTION	10	% Δ weight	Max.	MI 98 IN CC
	CORK PERCENTAGE	75	%	Min.	T-IF-02
MECHANICS	DIMENSIONAL RECOVERY (5 min)	95	%	Min.	UNE 56933
	EXTRACTION FORCE	25	daN	± 10	UNE 56933
	COMPRESSION FORCE	140	daN	± 15	88 IN CC
CHEMICAL	RESIDUAL PEROXIDE	0,2	mg/stopper	Max.	UNE 56929
	GLOBAL MIGRATION	10	mg/dm2	Max.	UNE-ISO 10106
MICROBIOLOGIC	BACTERIA	30	UFC/ stopper	Max.	UNE 56923
	MOLD AND YEAST	10	UFC/ stopper	Max.	UNE 56923
SPME/ GC/ MS ANALYSIS	2,4,6 –TCA,	0,9	ng/L	Max.	UNE 56930
	2,3,4,6 –TeCA, PCA ,Guayacol, Geosmina, Octanol, metilisoborneol, 2- isopropil-3metoxipirazina	< LD	ng/L	< LD	External
SENSORY	SENSORY DESVIATIONS	AQL 0.65. Method: water maceration.			

The products used for the manufacturing this product do not contain genetically modified organisms (GMOs) or allergens.

